

635



Product Description

635 is an extreme thin polyurethane open pore foam. In layer used, 635 makes windings very easily done.

635 is resistant to grease, Oil, Ointment, Body sweat.

Performance Features

Ideal for thin fixation without bubbles

Can be used for bubblefree application of polyester material.

Is used for skin protection under plaster and tape bandages

Technical information

	<i>unit</i>	<i>value</i>
density of product	kg/M3	24.8 +- 10 %
tear resistance	Kpa	138 - 193
maximal elongation	%	300 -340

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no wa for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure



AMERICAN BILRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

