

# 7007 & 7017



## Product Description

---

A 25-micron polyester film with a proprietary Therm-X based, thermosetting acrylic adhesive system.

## Performance Features

---

Tough, thin abrasion resistant tape used in electrical applications requiring temperature performance up to 130°C and a non-corrosive adhesive system.

## Applications

---

Tough, conformable and thin, these products are used in electrical applications where good solvent resistance is required.

## Technical information

	<b>7007</b>	<b>7017</b>
Insulation class (°C)	130	130
Total Thickness (mm)	0.063	0.063
Backing Thickness (mm)	0.025	0.025
Adhesion to Steel (N/25mm)	9.73	9.73
Dielectric Breakdown (kV)	5	5
Tensile Strength (N/25mm)	102	102
Elongation at Break (%)	100	100
Colour	Yellow	Clear
Adhesion System	Acrylic	Acrylic

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilTRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.  
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
e-mail: info@idealabi.com website: www.idealabi.com

