

701



Product Description

701 is a polyester film with a clear rubber-based pressure sensitive thermosetting adhesive.

Performance Features

It is a thin, tough and abrasion resistant tape for use in electrical applications requiring temperature performance up to 130°C and a non-corrosive adhesive system. It is conformable to many irregular surfaces.

Applications

It is used for transformers, capacitors and coils.

Technical information

Backing Thickness (mm)	0.023 ± 10%
Total Thickness (mm)	0.06 ± 10%
Peel Adhesion to Steel (N/25mm)	11.25
Peel Adhesion on Backing (N/25mm)	6.5
Elongation (%)	90
Tensile Strength (N/25mm)	100
Breakdown Voltage (kV)	4.5
Temperature Class B (°C)	130

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

