

# 702



## Product Description

702 is a clear polyester film with a yellow rubber-based pressure sensitive thermosetting adhesive system (RTS).

## Performance Features

As a thicker version of product 700, this tough and abrasion resistant tape is used for electrical applications requiring temperature performance up to 130°C and non-corrosive adhesive systems.

## Applications

It is comfortable to many irregular surfaces.

## Technical information

Carrier	Polyester
Adhesive	Yellow thermosetting rubber
Total Thickness (mm)	0.085
Carrier thickness (mm)	0.05
Elongation (%)	100
Adhesion to Steel (N/25mm)	11.25
Tensile Strength (N/25mm)	225
Dielectric Strength (kV)	8
Insulation Class (°C)	UL B / 130

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



**AMERICAN BILRITE INC.**  
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
e-mail: info@idealabi.com website: www.idealabi.com

