

# 7299



## Product Description

7299 is a 125-micron thick electrical grade fiberglass cloth coated with an efficient silicone adhesive.

## Performance Features

Tough abrasion resistance.  
Excellent mechanical and electrical properties.  
Highly conformable, no corrosion, UL approval.  
Flame retardant.  
High tensile strength.

## Applications

7299 meets requirements for most high temperature industrial needs.

## Technical information

Backing	Fiberglass fabric
Backing Thickness (mm)	0.14
Total Thickness (mm)	0.19
Adhesive	Silicone
Adhesion to Steel (N/25mm)	6.4
Tensile Strength (N/25mm)	441
Elongation (%)	15
Dielectric Strength (kV)	3
Insulation Class (°C)	UI H / 200
Temperature Range (°C)	-73 and +260
Colour	White

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



**AMERICAN BILTRITE INC.**  
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
e-mail: info@idealabi.com website: www.idealabi.com

