

Product Description

730XP is a 125-micron thick electrical grade fiberglass cloth tape with a highly efficient acrylic adhesive.

Performance Features

Excellent flagging and solvent resistance.
Tough abrasion resistance.
Comformable and edge-tear resistance
Solvent resistance.

Applications

730XP is used for covering coils, layers and wires as well as insulating crossovers.

Technical information

Backing	Fiberglass fabric
Backing Thickness (l (mm)	0.135
Total Thickness (mm)	0.18
Adhesion Type	Acrylic
Adhesion to Steel (N/25mm)	13.2
Tensile Strength (N/25mm)	588
Elongation (%)	17
Dielectric Strength (kV)	3.5
Insulation Class (°C)	UL F / 155
Temperature Range (°C)	Between -29 and +177
Colour	White

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

