

# 9180, 9185



## Product Description

A 25-micron polyester film with a silicone adhesive system.

## Performance Features

Tough, thin, abrasion resistant tape used in electrical applications requiring temperature performance up to 180°C and a non-corrosive adhesive system.

## Applications

Tough, conformable and thin, these products are used in electrical applications where good solvent resistance is required.

## Technical information

	<b>9180</b>	<b>9185</b>
Total Thickness (mm)	0.1	0.1
Adhesive Thickness	0.075	0.075
Backing Thickness (mm)	0.025	0.025
Adhesive System	Silicone	Silicone
Adhesion to Steel (N/25mm)	7	7
Tensile Strength (N/25mm)	100	100
Elongation at Break (%)	100	100
Colour	Red	Green

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BlitRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
e-mail: info@idealabi.com website: www.idealabi.com

