

# 9190



## Product Description

A 25 micron polyester film backing with a pressure sensitive silicone adhesive system.  
This product is engineered for applications where no/low residue is a requirement.

## Performance Features

- Highly conformable. Provides no-leak seals.
- Controlled unwind. Enhances manual or machine application.
- Polyester film substrate Allows for easy removal without danger of breakage or bath contamination.

## Applications

Designed to perform in all phases of masking operations for printed circuit board production.  
Protects curcuitry from splashes and chemical fumes.

## Technical Information

Total Thickness (mm)	0.075
Backing Thickness (mm)	0.025
Adhesive System	Silicone
Adhesion to Steel (N/25mm)	6.95
Tensile Strength (N/25mm)	102
Elongation at Break (%)	100%
Colour	Blue

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



**AMERICAN BILRITE INC.**  
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61

