

9217



Product Description

9217 is a polyester film with a pressure sensitive, state-of-the-art, halogen free silicone adhesive system.

Performance Features

Polyester film : Will not break or tear during application or removal
Halogen-free silicone adhesive system : Provides resistance to both chemical and heat degradation.
Assures an excellent bond without leaving residue.

Applications

9217 is used in a variety of splicing applications where chemical resistance and resistance to heat degradation are desired.

Technical information

Backing Thickness (mm)	0.05
Adhesive Thickness (mm)	0.035
Total Thickness (mm)	0.085
Tensile Strength (N/25mm)	222
Adhesion to Steel (N/25mm)	11
Elongation (%)	100
Adhesive	Silicone
Colour	Green

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

