

9548



Product Description

9548 is a 125-micron polyester film, coated with a pressure-sensitive silicone adhesive system.

Performance Features

- Polyester film substrate:* Strong performance. Allows for easy removal without danger of breakage or bath contamination.
- Silicone adhesive system:* Provides resistance to fumes and chemicals for no/low residue applications.

Applications

9548 is used for masking and composite bonding applications.

Technical information

Total Thickness (mm)	0.1625
Backing Thickness (mm)	0.125
Adhesive Thickness (mm)	0.0375
Adhesion to Steel (N/25mm)	11
Tensile Strength (N/25mm)	555
Elongation at Break (%)	120
Backing	Polyester film
Adhesive Type	Silicone
Colour	Blue

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

