

## Product Description

488AWF is 50-micron, alloy aluminium foil with a pressure sensitive adhesive and paper liner.

## Performance Features

- Dead Soft Aluminum Foil:* Conforms to irregular surfaces such as FSK facings and blends with the basic facing pattern. Foil as a vapor barrier assures integrity of the insulation system.
- Special rubber adhesive:* This aggressive adhesive, once applied, assures durable performance.
- Easy removable liner:* Saves labor, materials, and cost by providing consistent, predictable, performance as liner is removed for the final tape application.

## Applications

This product is used with fibreglass duct-board and on all seams and joints. It provides a dependable vapour barrier when applied to clean, dry surfaces

## Technical information

Backing thickness (mm)	0.05
Tensile Strength (N/25mm)	75
Adhesion to steel (N/25mm)	25
Elongation (%)	3
Backing	Aluminium foil
Adhesive type	Rubber
Colour	Silver

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



**AMERICAN BILRITE INC.**  
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
e-mail: [info@idealabi.com](mailto:info@idealabi.com) website: [www.idealabi.com](http://www.idealabi.com)

