

488ECO



Product Description

488ECO is a dead soft aluminium, 30-micron thick, pressure sensitive adhesive with removable paper liner.

Performance Features

Dead Soft Aluminum Foil: Conforms to irregular surfaces.
Special adhesive: Assures firm and long lasting bond.
Easy removable liner: Saves labor, materials, and cost by providing consistent, predictable, performance as liner is removed for the final tape application.

Applications

488ECO is for sealing duct and dual temperature insulation materials faced with aluminum. The foil bends with the facing and gives a strong, matching look. At the same time, taped joints assure the integrity of the insulation.

Technical information

Backing thickness (mm)	0.03
Tensile Strength (N/25mm)	53
Adhesion to steel (N/25mm)	25
Elongation (%)	3
Backing	Aluminium Foil
Adhesive type	Rubber
Colour	Silver
Liner	Paper

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

