

# 877



## Product Description

877 is an aluminium foil coated on one side with an acrylic adhesive and protected with a siliconized release liner.

## Performance Features

The acrylic adhesive requires no moisture, heat or special preparation prior to application.

## Applications

This product is used to seal seams and joints on metalized facings of insulator materials. It completes the vapour retardant layer at these locations to assure the integrity of the insulation system.

## Technical information

	<b>Average values</b>	<b>Test method</b>
Thickness (mm)	0.0355	PSTC-33
180° Peel Adhesion (N/25mm)	14	PSTC-1
Tensile Strength (N/25mm)	102	
Temperature Range	-20°C to +120°C	
Elongation (%)	11	

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



**AMERICAN BILRITE INC.**  
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
e-mail: info@idealabi.com website: www.idealabi.com

