

2100



Product Description

This product is a double-sided tissue tape coated with a solvent acrylic adhesive designed for permanent fixing, bonding and laminating applications.

Performance Features

This is a high performance tape giving good adhesion, peel and shear performance. It is plasticiser and UV resistant.

Applications

This tape can be used to bond a wide variety of substrates. It is also ideal for paper/board splicing.

Technical information

Adhesive	Acrylic
Thickness of Carrier Tissue (mm)	0.03
Thickness of Adhesive (mm)	0.07
Total Thickness (mm)	0.1
Adhesion to Steel (N/25mm)	11.76
Temperature Resistance (°C): <i>Short term</i>	180°
<i>Long term</i>	140°
Elongation (%)	3 ± 1

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

