

# 2165



## Product Description

---

2165 is a high temperature, high performance, double coated tissue paper tape. It has a two-sided coating of a special, high grip, non-polar, acrylic-based, pressure sensitive adhesive.

## Performance Features

---

High quality and strong holding power acrylic adhesive allows for use on a wide variety of surfaces.  
Excellent resistance to heat, weathering and thermal creep.  
Treated, release paper liner allows for easy handling.  
No known hazard.

## Applications

---

High adhesion and strength on a wide variety of materials including sails  
Bonding to many irregular or textured surfaces (especially on non-polar materials), due to the thick, non-polar acrylic adhesive.  
Ideal for paper/board splicing.

## Technical information

Adhesive	Acrylic
Thickness of Carrier (mm)	0.03
Thickness of Adhesive (mm)	0.07 x 2
Total Thickness (mm)	0.17
Adhesion to Steel (N/25mm)	19.6
Tensile Strength (N/25mm)	19.6
Temperature Range (°C)	Between -40 and +150

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



**AMERICAN BILRITE INC.**  
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
e-mail: info@idealabi.com website: www.idealabi.com

