

# 2888



## Product Description

2888 is a double-sided tape with a rubber based hotmelt adhesive, a polypropylene film carrier and a brown siliconized paper liner.

## Performance Features

The tape has a good initial adhesion and is resistant to plastified products.

## Applications

2888 is a universal tape for a wide variety of uses.

## Technical information

Carrier	Polypropylene film
Liner	Siliconized paper
Adhesive	Rubber based hotmelt
Total Thickness without liner (mm)	0.085
Adhesion to Steel AFERA 4001 (N/25mm)	30
Temperature Range (°C)	Between -10 and +60

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



**AMERICAN BILRITE INC.**  
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
e-mail: info@idealabi.com website: www.idealabi.com

