

7932



Product Description

7932 is a general purpose, high modulus PFTE tape.

Performance Features

Excellent release and temperature resistance.
Very simple application, due to the tape having no backing liner.
Strips easily after use.

Applications

Ideal for many applications including: temporary tool surface repairs, sealing of split moulds to prevent resin penetration and where localised tool release in tight angles is required.

Technical information

Maximum use temperature (°C)	230
Carrier Thickness (mm)	0.05
Adhesive Thickness (mm)	0.034
Total Thickness(mm)	0.084
Elongation (%)	140
Adhesion (N/25mm)	7
Breaking Strength (N/25mm)	112.5 (Silicone Adhesive)
Insulation class (°C)	UL H/180
Colour	Brown

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

