

91718



Product Description

91718 is an acrylic double sided PET film tape.

Performance Features

Excellent solvent resistance.
Excellent durability against heat and sunlight.
Solvent-free type, good plasticizer resistance.
Good reworkability and converting performance.

Applications

Bonding thin plastic panels for electronic products.
Mobile phone internal part bonding.
Light weight stainless steel and aluminium bonding.
LCD module inter-face and FPC bonding.

Technical information

| | |
|-----------------------------|-------------|
| Total Thickness (mm) | 0.24 |
| Carrier Thickness (mm) | 0.012 |
| Adhesive Thickness (mm) | 0.11 |
| Adhesion to Steel (N/25mm) | 19 |
| Temperature Resistance (°C) | -20 to +150 |
| Carrier | PET film |
| Colour | Transparent |

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

