

## Product Description

9235 is a double sided polyester adhesive tape with a thin carrier. This tape has a carrier of 12-micron polyester, which is strong yet thin, making it suitable for a wide range of applications. The product also has a high performance solvent acrylic adhesive, suitable for demanding applications. The liner is a standard PE coated paper of 105 gr.with a differential silicone treatment, with easy release. It is moisture stable.

## Performance Features

Very good shear and peel performance.  
 Performs well in severe climatic conditions at low and elevated temperatures.  
 Good resistance to chemicals and UV light.

## Applications

9235 is suitable for a wide variety of general purpose applications, where a thin tape with good all round performance is required. It is suitable for foam laminating and for bonding material with a smooth surface. It can be used for light assembly and fixing applications and for bonding thin flexible material and fabrics.

## Technical information

Adhesive	Solvent acrylic
Carrier Thickness (mm)	0.012
Adhesive Thickness (mm)	0.058
Total Thickness (mm)	0.07
Colour	Clear
Carrier	12 micron polyester
Liner Type	White PE coated paper
Liner Weight (grams)	105
180°C Peel Adhesion AFERA 4001 10 minutes (N/25mm)	10.7
180°C Peel Adhesion AFERA 4001 24 hours (N/25mm)	14.2
Temperature Range °C	'''
Tack AFERA 4015 (N/25mm)	4.6

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



**AMERICAN BILRITE INC.**  
 EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
 tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
 e-mail: info@idealabi.com website: www.idealabi.com

