

93900



Product Description

93900 is a double sided polyethylene foam tape with acrylic adhesive.

Performance Features

Functions well as an isolation tape against vibration and impact.
Functions well on steel and plastic panels.
Good adhesion to foam.
Easy application on curved surfaces.
Easy application on parts that require strong cohesion.

Applications

Recommended for exterior mounting in the automotive industry (side moulding, emblem and also rear view mirror)

Technical information

Tape Thickness (mm)	0.95
180°C Peel Adhesion to Steel (N/25mm)	21
Tensile Strength (N/25mm)	55
Temperature Resistance (°C)	Between -20 and +120
Colour	White/Black
Liner	Red PE

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

