

# 7231



## Product Description

ProtecRite® 7231 is a 2.5 mil Polyolefin film developed for protection of residential and commercial carpeting. The easy unwound film has the advantage of being puncture resistant.

## Performance Features

- Removable            Clean and stain-free removal
- Very Strong           This film is puncture resistant.
- Easy Application      Easy unwind
- Printable              Can be supplied imprinted with your logo, signature, application instructions etc ...

## Applications

7231 can be used for the protection of carpeting; commercial and residential, painted textured surfaces, matt polycarbonate and textured marble.

## Technical Information

Total Thickness	66 µ
Adhesion to Steel	7.7 N/25mm
Tensile Strength	30 N/25mm
Elongation	190%
Adhesive Type	Acrylic

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



**AMERICAN BILTRITE INC.**  
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51    fax: +32 (0)55/23.51.61

