

8510



Product Description

ProtecRite® 8510 is a 3 mil UV-stable polyolefin film with a solvent rubber adhesive system. The adhesive system offers uniform adhesion over a variety of surfaces and can be applied over partially cured paints and coatings.

Performance Features

- Removable Clean and stain-free removal, even after application for extended time periods.
- Uniform Adhesion This specially designed adhesive system resists build.
- Outdoor Storage UV-resistant up to 6 months.
- Printable Can be supplied imprinted with your logo, signature, application instructions etc ...

Applications

8510 can be used for light to medium fabrication and protection of partially cured paints and coatings.

Technical Information

Total Thickness	72 μ
Adhesion to Steel	3 N/25mm
Tensile Strength	33 N/25mm
Elongation	900%
Adhesive Type	Rubber

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61

