

930A



Product Description

930A is a pressure sensitive adhesive coated white UV stabilized polyolefin film masking.

An alternative to shrink wrap or can be used to spot treat graphics, glitter gels, painted surfaces before applying shrink wrap to protect from abrasion damage caused during transit.

Performance Features

- REMOVABLE : Clean, stain free, one piece removal even after extend application.
- CONFORMABLE Product remains intact even over bends and curved surfaces.
- NO EDGE LIFT : Adheres evenly to the applied surface and resists edge lift even during transportation.

Applications

Transit masking before shrink wrapping eliminates chafing.

Technical Information

Total Thickness	50 μ
Adhesive type	Rubber
Adhesion to steel	4.45 N/25mm
Tensile strength	9900 psi
Elongation at break	600%
Backing	Polyolefin film
Colour	White

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilTRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

