

Product Description

Autowrap 127 is a pressure sensitive, white, UV stabilized polyolefin film masking. and 127 is designed to protect textured exterior and interior finishes during assembly and transportation.

Performance Features

Removable: Clean, stain free, one piece removal even after extend application.
 Conformable: Product remains intact even over bends and curved surfaces.
 No edge lift: Adheres evenly to the applied surface and resists edge lift even during transportation.

Applications

127 is suggested for protection of textured exterior and interior parts including exterior mold-in-colour plastics and interior plastic surfaces during shipment to dealer and storage.

NOT RECOMMENDED FOR PAINTED SURFACES

Technical information

Total Thickness (mm)	0.089
Adhesive type	Solvent acrylic
Adhesion to Steel (N/25mm)	11.12
Tensile Strength (N/25mm)	114.98
Elongation at Break (%)	500
Backing	Polyolefin
Colour	White & Clear

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



Industriezone 23, B-9600 Ronse, Belgium
 tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
 e-mail: info@idealabi.com website: www.idealabi.com

