

# 410



## Product Description

410 Autowrap is a pressure sensitive, adhesive coated, white UV stabilized polyolefin film masking.

It is designed to protect automotive finishes and trim during assembly and transit.

## Performance Features

*Removable:* Clean, stain free, one piece removal even after extend application.

*Conformable:* Product remains intact even over bends and curved surfaces

*No edge lift:* Adheres evenly to the applied surface and resists edge lift even during transportation.

## Applications

410 is suggested for antimutilation protection of painted automotive finishes, body, bumper and tail lamp during shipment to the dealer and storage.

## Technical information

Total Thickness (mm)	0.1025
Tensile strength (N/25mm)	113.13
Elongation (%)	740
Backing	Polyolefin film
Adhesive Type	Rubber
Colour	White
Adhesion (N/25mm)	3.892
Shelf life (from time of manufacture)	24 months

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
e-mail: info@idealabi.com website: www.idealabi.com

