

8510



Product Description

8510 Protectrite is a 75-micron UV stable polyolefin film with a solvent rubber adhesive system.

Performance Features

<i>Removable:</i>	Clean, stain free, one piece removal even after extend application.
<i>Special adhesion:</i>	Uniform adhesion over a variety of surfaces. Resists build. Can be applied over partially cured paints & coatings.
<i>Outdoor storage:</i>	UV resistant up to 6 months.

Applications

8510 is designed for the protection of metal and metal-coated surfaces during fabrication.

Technical information

Total thickness (mm)	0.075
Tensile Strength (N/25mm)	42.05
Elongation (%)	900
Backing	Polyolefin film
Adhesive type	Rubber
Color	Blue, Clear
90° Adhesion (N/25mm)	3.058
Printable Surface	Y
Shelf life (from time of manufacture)	24 months

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

