

895



Product Description

895 Autowrap is a clear, pressure sensitive adhesive coated, UV stabilized polyolefin film masking.

Performance Features

Removable: Clean, stain free, one piece removal even after extend application.
Conformable: Product remains intact even over bends and curved surfaces.
No edge lift: Adheres evenly to the applied surface and resists edge lift even during transportation.

Applications

895 is designed for automotive paint systems protection during transit to the dealer and storage, and automotive components shipped to assembly plants.

Technical information

| | |
|---------------------------------------|-----------------|
| Total thickness (mm) | 0.055 |
| Tensile Strength (N/25mm) | 79 |
| Elongation (%) | 650 |
| Backing | Polyolefin film |
| Adhesive type | Rubber |
| Color | Clear |
| 90° Adhesion (N/25mm) | 3.058 |
| Shelf life (from time of manufacture) | 24 months |

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

