

930A



Product Description

Autowrap 930A is a white pressure sensitive adhesive coated UV stabilized polyolefin film masking.

Performance Features

Removable: Clean, stain free, one piece removal even after extend application.
Conformable: Product remains intact even over bends and curved surfaces.
No edge lift: Adheres evenly to the applied surface and resists edge lift even during transportation.

Applications

930A is designed for the protection of automotive finishes during transit to the dealer and storage.

Technical information

Total thickness (mm)	0.05
Tensile Strength (N/25mm)	86.72
Elongation (%)	600
Backing	Polyolefin film
Adhesive type	Rubber
Color	White
90° Adhesion (N/25mm)	4.45
Shelf life (from time of manufacture)	24 months

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

