

1522



Product description

ProtecRite® 1522 is a 4.5 mil clear polypropylene masking film with a custom formulated high tack rubber based adhesive system. This tape is especially designed to protect screen-printed plastics and metals where both textured and smooth surfaces may be utilized on the same part.

Performance features

- Removable: clean, stain-free and one-piece removal, even after extended outdoor application
- Conformable: product remains intact, even over bends and curved surfaces
- Easy Application: can be supplied pre-cut to wheel shops for easy application

Applications

1522 can be used for protection on textured vinyls, acrylic and urethane coated vinyls and non-coated vinyls.

Technical information

Film thickness (without adhesive)	98 µm
Adhesive thickness	13 µm
Total thickness	111 µm
Adhesive type	rubber
Adhesive strength (adhesion to steel)	5.20 N/25mm
Core colour	N/A
Tensile strength	66 N/25mm
Elongation at break	600%
Shelf life	24 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American Biltrite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

