

7201



Product description

ProtecRite® 7201 is a 2 mil Co-extruded Polyethylene film developed for general surface protection and/or shipping. The custom formulated acrylic adhesive offers a "lower adhesion" product with minimal adhesion build even during extended application.

Performance features

- Removable: clean and stain-free removal, even after application for extended time periods
- Conformable: light gauge backing offers increased conformability and flexibility
- Easy Application: the controlled unwind allows application using either manual or automatic methods
- Printable: can be supplied imprinted with your logo, signature, application instructions etc.

Applications

7201 can be used for protection on bright annealed stainless, mirror finish stainless, smooth polycarbonate; gloss painted surfaces.

Technical information

Film thickness (without adhesive)	38 µm
Adhesive thickness	6 µm
Total thickness	44 µm
Adhesive type	acrylic
Adhesive strength (adhesion to steel)	0.41 N/25mm
Core colour	N/A
Tensile strength	31 N/25mm
Elongation at break	600%
Shelf life (from time of manufacture)	18 months (21 °C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

