

7322



Product description

ProtecRite® 7322 is a 3 mil Low Density Polyethylene film designed for protection of highly textured surfaces or surfaces requiring a higher adhesion product during shipping and/or moderate fabrication. The adhesive system offers a "high adhesion" product with minimal adhesion build.

Performance features

- Removable: clean and stain-free removal
- Conformable: product remains intact, even during moderate bending
- Versatile: available direct wound for machine lamination or reverse wound to provide easy hand application
- Printability: cannot be imprinted

Applications

7322 can be suggested for textured laminates, textured plastics & vinyls, painted "textured" steel & aluminum and low pile carpets.

Technical information

Film thickness (without adhesive)	56 µm
Adhesive thickness	13 µm
Total thickness	69 µm
Adhesive type	acrylic
Adhesive strength (adhesion to steel)	6 N/25mm
Core colour	N/A
Tensile strength	26 N/25mm
Elongation at break	325%
Shelf life (from time of manufacture)	18 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

