

7405



Product description

ProtecRite® 7405 is a 4 mil Low Density Polyethylene film designed for protection of relatively smooth to medium textured finishes during fabrication and/or shipping. The custom formulated acrylic adhesive offers a "medium adhesion" product with minimal adhesion build.

Performance features

- Removable: clean and stain-free removal, even after application for extended time periods
- Conformable: product remains intact, even during extreme bending
- Easy application: the controlled unwind allows for application using manual or automatic methods
- Printable: can be supplied imprinted with your logo, signature, application instructions etc.

Applications

7405 can be suggested for the protection of medium polished stainless steel, painted metals, smooth & matt polycarbonate, anodized aluminum and mill finish aluminum.

Technical information

Film thickness (without adhesive)	80 µm
Adhesive thickness	9 µm
Total thickness	89 µm
Adhesive type	acrylic
Adhesive strength (adhesion to steel)	1.4 N/25mm
Core colour	N/A
Tensile strength	39 N/25mm
Elongation at break	425%
Shelf life (from time of manufacture)	12 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

