

# 7431



## Product description

---

ProtecRite® 7431 is a 4 mil clear Low Density Polypropylene film specially designed for the protection of residential and commercial carpeting. This easily unwound film has the added advantage of being puncture resistant.

## Applications

---

7431 can be used for the protection of carpeting; commercial & residential, painted textured surfaces, matt polycarbonate and textured marble.

## Technical information

Film thickness (without adhesive)	80 µm
Adhesive thickness	9 µm
Total thickness	89 µm
Adhesive type	acrylic
Adhesive strength (adhesion to steel)	10.8 N/25mm
Core colour	N/A
Tensile strength	39 N/25mm
Elongation at break	425%
Shelf life (from time of manufacture)	18 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



**AMERICAN BILTRITE INC.**  
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
e-mail: [info@idealabi.com](mailto:info@idealabi.com) website: [www.idealabi.com](http://www.idealabi.com)

