

7522



Product description

ProtecRite® 7522 is a clear 5 mil Low Density Polyethelene film designed for protection of highly textured surfaces requiring a higher adhesion product during moderate fabrication and/or shipping. The custom acrylic adhesive system offers "high adhesion" with minimal adhesion build.

Performance features

- Removable: clean and stain-free removal, even after application for extended time periods
- Durable: the tough 5 mil product is durable and resists scratching and abrasion
- Printable: can be supplied imprinted with your logo, signature, application instructions etc.

Applications

7522 can be suggested for textured laminates, textured plastics & vinyls, painted "textured" steel & aluminum and low pile carpets.

Technical information

Film thickness (without adhesive)	106 µm
Adhesive thickness	9 µm
Total thickness	115 µm
Adhesive type	acrylic
Adhesive strength (adhesion to steel)	6.5 N/25mm
Core colour	N/A
Tensile strength	52 N/25mm
Elongation at break	380%
Shelf life (from time of manufacture)	18 months (21 °C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

