

8502



Product description

ProtecRite® 8502 is a 2 mil polypropylene film masking with a solvent rubber adhesive system and is especially designed for applications where die-cutting is typically utilized. The solvent rubber adhesive offers a uniform adhesion over a variety of surfaces.

Applications

8502 can be used for sublimation of trophy stock metal, lacquer-coated aluminum, die-cutting applications.

Technical information

Film thickness (without adhesive)	43 µm
Adhesive thickness	10 µm
Total thickness	53 µm
Adhesive type	rubber
Adhesive strength (adhesion to steel)	3 N/25mm
Core colour	N/A
Tensile strength	53 N/25mm
Elongation at break	600%
Shelf life (from time of manufacture)	24 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

