

6882

ProtecRite Digital

Product description

ProtecRite® Digital 6882 is a medium tack application tape featuring a premium, moisture resistant saturated paper backing with specially formulated latex, pressure sensitive adhesive. This application tape is specially designed for protection of UV-printed graphics.

Applications

6882 is especially designed for mounting and protecting large format digital prints and is ideal for applications where superior dimensional stability and humidity resistance is required. This application tape adheres to textured and smooth surfaces and releases cleanly after installation; it allows you to apply the tape immediately after printing with UV-cured inks without damaging your graphic when the application tape is removed.

Technical information

Paper thickness (without adhesive)	111 µm
Adhesive thickness	29 µm
Total thickness	140 µm
Adhesive type	natural rubber latex
Adhesive strength (adhesion to steel)	3.8 N/25mm (medium tack)
Core colour	white
Tensile strength	92 N/25mm
Elongation at break	13%
Shelf life (from time of manufacture)	30 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

