

304



Product Description

304 is a natural crepe, pressure sensitive adhesive.

Performance Features

Conforms to irregular surfaces assuring maximum adhesive.
Grabs quickly and holds securely to many types of surfaces.
Resists failure when package is exposed to moisture, oil or some solvent.
Easy to use, no breaks.

Applications

It is used for general purpose packaging, holding and splicing.
It is also acceptable for general masking applications.

Technical information

Adhesive System	Acrylic
Backing Thickness (mm)	0.115
Adhesive Thickness (mm)	0.05
Total Thickness (mm)	0.165
Adhesion to Steel (N/25mm)	8.9
Tensile Strength (N/25mm)	111.18
Elongation (%)	6
Colour	Natural

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

