

# 5603 & 5613



## Product Description

It is a high quality fabric based tape with a good anti-ageing and temperature resistant rubber adhesive.

The carrier of this tape is a strong, conformable weather and waterproof PE coated film which is tearable by hand and comes in silver (5603) and in black (5613).

## Performance Features

Special adhesive layer, high adhesive weight and strong but conformable PE coated film. Anti-ageing and wide temperature range.

## Applications

5603 and 5613 can be used within applications with dirty, dusty or rough and uneven surfaces.

The tape can be used for indoor and outdoor applications such as sealing seams and holes.

## Technical information

Carrier	LDPE + 63 Mesh
Adhesive	Rubber + Resin
Thickness of Carrier (mm)	0.19
Thickness of Adhesive (mm)	0.1
Total Thickness (mm)	0.29
Adhesion to Steel (N/25mm)	13.475
Tensile Strength (N/25mm)	115.15
Temperatrue Range (°C)	

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is not responsible for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



**AMERICAN BILRITE INC.**  
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium  
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61  
e-mail: info@idealabi.com website: www.idealabi.com

