

PT115



Product Description

W972 is a UV stable white 87.5-micron olefin film with solvent acrylic adhesive.

Performance Features

Removable: Clean, stain free, one piece removal even after extend application.
Conformable: Product remains intact even over bends and curved surfaces.
No edge lift: Adheres evenly to the applied surface and resists edge lift even during transportation.

Applications

It is suggested for antimutilation protection of painted automotive finishes, body, bumper and tail lamp during shipment to dealer and storage.

Technical information

	Nominal Values	Test Method
Total Thickness (mm)	0.119	PSTC-33
90° Peel Adhesion (N/25mm)	10	PSTC-101
Tensile strength (N/25mm):		
MD	78.75	ASTM D882
TD	51.25	ASTM D882
Elongation at break (%):		
MD	825	ASTM D882
TD	800	ASTM D882

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

