

6798



Product description

TransferRite® 6798 is a super high tack application tape featuring a premium, moisture resistant saturated paper backing with specially formulated latex, pressure sensitive adhesive.

Applications

Can be used in sign shops for highly textured vinyls (e.g. etched glass vinyl), high gloss urethane top-coated vinyls and can also be used in screen printing.

6798 is ideal for applications where superior dimensional stability, humidity resistance, or long term storage stability is required.

Technical information

Paper thickness (without adhesive)	111 µm
Adhesive thickness	34 µm
Total thickness	145 µm
Adhesive type	natural rubber latex
Adhesive strength (adhesion to steel)	7.7 N/25mm (super high tack)
Core colour	red
Tensile strength	92 N/25mm
Elongation at break	5%
Shelf life (from time of manufacture)	12 months (21°C / 50% humidity)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

