

4114



Product Description

LabelRite 4114 label stock is a 100-micron UV-stable polyolefin film applied to a 50# SCK paper liner.

Performance Features

- Removable:* Clean, stain free, one piece removal even after extend application
- Conformable:* Product remains intact even over bends and curved surfaces.
- No edge lift:* Adheres evenly to the applied surface and resists edge lift even during transportation.
- Excellent adhesion:* High performance solvent rubber adhesive system.

Applications

4141 is suggested for automotive and appliance paints, polycarbonate (coated or non-coated), glass, defect marking and metals.

Technical information

Backing thickness (mm)	0.1
Liner Thickness (mm)	0.088
Total thickness (mm)	0.1875
Tensile Strength (N/25mm)	67.52
Backing	Polyolefin film
Adhesive type	Rubber
Color	White
Printable surface	Y
Liner Type	50# SCK
Shelf life (from time of manufacture)	24 months

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BilRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

