

PT348



Product Description

PT 348 is a pressure sensitive, white, UV stabilized polyolefin film. PT 348 is designed to protect textures exterior and interior finished and also to protect wheels during assembly and transportation.

Performance Features

PT348 is also designed for protection of alloy wheels. It has a long UV resistance (min. 9 months) and can cope with high temperature (up to 120°C for short notice).

Applications

PT348 is suggested for use in the protection of textured exterior and interior parts including exterior mold-in-colour plastic surfaces during shipment to dealer and storage.

Technical information

Total Thickness	0.114
Tensile	6300 psi
Elongation	550%
Adhesion	7.2
Backing:	Polyolefin
Adhesive:	Acrylic
Colour:	White

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.



AMERICAN BILTRITE INC.
EXCELLENCE THROUGH QUALITY

Industriezone 23, B-9600 Ronse, Belgium
tel: +32 (0)55/23.51.51 fax: +32 (0)55/23.51.61
e-mail: info@idealabi.com website: www.idealabi.com

